



**HAVELLS**

enviro  
HARNESSING LIGHT. HARVESTING ENERGY.

**LET THE SUN POWER  
YOUR BUSINESS**



## **HAVELLS ENVIRO GTi 255 kW-HV**

- Designed for 1500V DC Application
- 12 MPPT with 40 % DC Overload
- Compatible with Bi-facial PV Modules with 15 Amp current per string
- AC & DC Side TYPE-II SPD





## TECHNICAL SPECIFICATION

PARAMETER	ENVIRO GTi 255 kW- HV
<b>INPUT (DC)</b>	
Max. input voltage	1500 V
Rated input voltage	1080 V
Start-up voltage	550 V
MPPT operating voltage range	500 V~1500 V
Full power MPPT voltage range	800 V~1300 V
Number of MPP trackers	12
Number for DC inputs	24
Max. input current per MPPT	30A*12
Max. input short circuit current per MPPT	50A*12
<b>OUTPUT (AC)</b>	
Rated output power	255 kW
Maximum apparent power	255 kVA @30°C / 235 kVA@40 °C / 220 kVA @50 °C
Max. Output current	184 A
Nominal grid voltage	3/PE, 800 Vac
Grid voltage range	640 Vac~920 Vac
Nominal frequency	50 Hz / 60 Hz
Grid frequency range	45~55Hz / 55~ 65Hz (according to local standard)
Active power adjustable range	0~100 %
THDi	<3 %
Power factor	1 default (-0.8...+0.8 adjustable)
Power factor	1 default (-0.8...+0.8 adjustable)
<b>PERFORMANCE</b>	
Max efficiency	99.02 %
European Weighted efficiency	98.5 %
MPPT efficiency	>99.9 %
Self-Consumption at night	< 2 W
<b>STANDARD</b>	
EMC	EN 61000-6-2, EN 61000-6-4 (under certification)
Safety standard	IEC62109-1/2, IEC62116, IEC61727, IEC-61683, IEC60068(1,2,14,30) (under certification)
<b>PROTECTION</b>	
DC reverse polarity protection	Yes
Anti-Islanding Protection	Yes
Leakage current protection	Yes
Ground fault monitoring	Yes
PV-array string fault monitoring	Yes
Zero voltage ride through	Yes
DC Switch	Yes
Anti-PID function	Yes
AFCI protection	Yes
Protection class/ overvoltage category	I/III
Input/ output SPD	PV: Type II standard, AC: Type II Standard

## TECHNICAL SPECIFICATION

PARAMETER	ENVIRO GTi 255 kW- HV
<b>GENERAL DATA</b>	
Topology	Transformer less
Ambient temperature range	-30 ~+60
Relative humidity	0% 100 %
Cooling	Smart forced air cooling
Max. altitude	4000 m
Noise	≤60 dB
Mounting	Wall mount
Communication	WiFi /GPRS /RS485/PLC/Bluetooth optional
Operation data storage	25 years
Display	LCD& Bluetooth
Self-consumption at night	<2 W
Degree of protection	IP66
Dimension	1100.5 mm × 713.5 mm × 368 mm
Weight	100 kg



---

**REGIONAL & BRANCH OFFICES:**

**NORTH - REGIONAL OFFICE: Corporate Office:** QRG Towers, 2D, Sector-126, Expressway, Noida-201304, Tel: 0120-3331000, **Delhi:** Tel: 011-47676700, 23888200, **Chandigarh:** Tel: 0172-4232400-401, **Dehradun:** Tel: 0135-6670202, **Noida / Haryana:** Tel: 0120-3331000, **Ludhiana:** Tel: 0161-4676000 / 24, **Jammu:** Tel: 0191-2478330, 2479330, **Sri Nagar:** Tel: 0194-2490431, **Jaipur:** Tel: 0141-3914645, 3988210 **Jodhpur:** Tel: 0291-9214201640 / 45, **Lucknow:** Tel: 0522-6672100, **Kanpur:** Tel: 0512-6710400, 6710409

**EAST - REGIONAL OFFICE: Kolkata:** ICC Tower, 5th Floor, 4 India Exchange Place, Kolkata-700001, Tel: 033-40129851 / 52, **Bhubaneshwar:** Tel: 0674-6668101/102/103/104, **Guwahati:** Tel: 0361-2134521, 2458923, 2460355, **Siliguri:** Tel: 0353-2525907, **Ranchi:** 0651-2244861, 2244862, 2244864, 2244868, 2244869, **Jamshedpur:** Tel: 0657-6542492, 09234369436, **Patna:** Tel: 0612-2207221, 2207222, 2207223, 2655518

**WEST - REGIONAL OFFICE: Mumbai:** 1271, Solitaire Corporate Park, Bldg. No. 12, 7th Floor, Andheri - Ghatkopar Link Road, Chakala, Andheri (East), Mumbai- 400093. Ph.: 022 - 67298600-602, **Ahmedabad:** Tel: 079-40061111, 40060738-740, **Indore:** Tel: 0731-2572340-41, 4009998 (Airtel), **Rajkot:** Tel: 0281-2481112, 2921212, **Nagpur:** Tel: 0712-2240932, 2242692, 2242699 **Pune:** Tel: 020-64016413 / 14, **Raipur:** Tel: 0771-4243400 / 01, **Surat:** Tel: 0261-2350137, 9979890137, **Jabalpur:** Tel: 0761-4064491

**SOUTH - REGIONAL OFFICE: Chennai:** Sigapi Achi Building, No. 18 / 3, 6th Floor, Rukmani Lakshmi Pathy Road, Egmore, Chennai-600008, Tel: 044-42280600, 605, **Bangalore:** Tel: 080-49075000, **Coimbatore:** Tel: 0422-4550200, 2305199, 2306199, **Hyderabad:** Tel: 040-27533372, 27533355, 27533632, 66320407/0408/6401/6402, **Kochi:** Tel: 0484-4099000, **Vizag:** Tel: 0891-6514339, **Vijayawada:** Tel: +91-9247058847/57, **Calicut:** 0495-4019194, **Madurai:** 0452-4267022, **Trivandrum:** 0471-4015323, **Hubli:** 09448146028, **Trichy:** 09944460160

Representative Offices: • Goa • Solapur • Gwalior • Kathmandu • Bhopal

---

Actual products may vary in colour, design, description and colour combination etc.  
Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication. Specifications & performance data are constantly changing.  
Current details should therefore be checked with Havells Group.  
"Copyright Subsists. Imitation of trade dress, graphics and color scheme of this document is a punishable offence."

---



**HAVELLS**

**Havells India Ltd.**

QRG Towers, 2D, Sector -126, Expressway, Noida - 201 304 (UP), Ph. +91-120-3331000,

E-mail: [marketing@havells.com](mailto:marketing@havells.com), [www.havells.com](http://www.havells.com)

Consumer Care No.: 08045 77 1313 (All Connections), 011-4166 0303 (Landline)

Join us on Facebook at [www.facebook.com/havells](http://www.facebook.com/havells) and share your ways to save the planet!

CIN - L31900DL1983PLC016304.

Scan the QR Code  
to download  
Havells mCatalogue

